

## DESK MASTER 12 PROFESSIONAL LP

#### DISPENSER FEATURES

| Dispensing technology                            | Alfa's patented pump   |
|--|--|
| Dispensing flow                                  | Simultaneous   |
| Colorants canisters configuration                | 12   |
| Colorants canisters capacity                     | 31-61  |
| Colorants pump flow rate                         | 0.2 l/min - 0.4 l/min  |
| Colorants minimum dispensed quantity             | 1/768 fl oz (0.038 cc)   |
| Colorants canisters material                     | POM (acetalic resin)   |
| Semifinished products canisters configuration    | 2 x 6l and 2 x 3l  |
| Semifinished products pump flow rate             | 0.4 l/min - 3 l/min  |
| Semifinished products minimum dispensed quantity | 1/74 fl oz (0.4 cc)  |
| Semifinished products canisters material         | AISI 304/ POM  |
| Canister stirring/ Recirculation                 | Pre-set (variable timing function available)                   |
| Accuracy   | * ±1%  |
| Valve type                                       | Three way valve  |
| Nozzle closure system                            | Automatic cap  |
| POWER SUPPLY / MACHINE ENVIRONMENT               |  |
| Power supply                                     | Single phase 100-240 V   |
| Frequency  | 50/60 Hz   |
| Fuses  | 5X20 mm (2pcs) – T3.15A-250V                                   |
| Maximum power absorption                         | 400W max   |
| Working temperature (Celsius)                    | 15° to 35°   |
| Relative humidity                                | From 5% to 85% (without condensation)                          |
| ATEX compliant                                   | No   |
| EQUIPMENT FEATURES                               |  |
| Embedded PC                                      | Standard   |
| Router   | Standard   |
| Ultrasonic humidifier                            | Option   |
| Dispensing head custom color                     | Option   |
| Can hole detector                                | Option   |
| Automatic shelf                                  | Option   |
| Roller Conveyor                                  | Option   |
| DISPENSER DIMENSION                              |  |
| Length   | 154 cm (60 in)   |
| Depth  | 115 cm (45 in)   |
|  |  |
| Height   | Working surface 95 cm (37 in) - Dispensing head 104 cm (41 in) |
| Height<br>Footprint                              |  |
| ·  | Working surface 95 cm (37 in) - Dispensing head 104 cm (41 in) |

\*Valuesaffected by the nature of the colorants / semifinished products and their rheological properties

The manufacturer declares under its sole responsibility that the machine to which this declaration relates, complies with the essential requirements of the following directives:

Machine Directive 2006/42/CE, Low Voltage Directive 2014/35/UE and Electromagnetic Compatibility Directive 2014/30/UE.



## DESK MASTER 12 HP

| Colorants canisters configuration             | Up to 12   |  |
|---|--|--|
| Semifinished products canisters configuration | 2x 30L and 2 x 50L   |  |
| Length  | 154 cm (60 in)   |  |
| Depth   | 115 cm (45 in)   |  |
| Height  | Working surface 95 cm (37 in) - Dispensing head 104 cm (41 in) |  |
| Footprint                                     | 1.77 sq mt   |  |
| \   |  |  |

Weight

### DESK MASTER 16 LP

| Colorants canisters configuration             | 16   |
|---|--|
| Semifinished products canisters configuration | 2 x 6L and 2 x 30L   |
| Length  | 208 cm (81 in)   |
| Depth   | 115 cm (45 in)   |
| Height  | Working surface 95 cm (37 in) - Dispensing head 104 cm (41 in) |
| Footprint                                     | 2.4 sq mt  |

# DESK MASTER 16 HP

| Colorants canisters configuration             | 16   |
|---|--|
| Semifinished products canisters configuration | 2x 30L and 2 x 50L   |
| Length  | 208 cm (81 in)   |
| Depth   | 115 cm (45 in)   |
| Height  | Working surface 95 cm (37 in) - Dispensing head 104 cm (41 in) |
| Footprint                                     | 2.4 sq mt  |